

**MORBARK** 

MORBARK

T



## **FEATURES AND BENEFITS**

- Large dedicated work/inspection area gives easy access to engine and hydraulic components.
- Kawasaki direct drive flail motors allow for adjustments of up to 578 RPM.

ONE FL

 Segmented flail drum provides better wear life than traditional tubular style drums.





GENERAL	US	METRIC
Length	24'1.5"	7.35 m
Height	10'7.5"	3.24 m
Width	9'9.75"	3.0 m
Gross Weight (approximate)	54,100 lb	24,539 kg
Infeed Opening	56" x 23"	142.24 cm x 58.42 cm
Engine	CAT	
Horsepower	375 HP	279 kW
Fuel Capacity (tank)	230 gallons	870 litres
Hydraulic Oil	200 gallons	757 litres
Tracks	CAT 320L 500mm Triple Grousers	

Specifications may vary with equipment options

## **EQUIPMENT HIGHLIGHTS**

- One top hydraulically driven feed roller mounted on a yoke assembly
- Two stationary bottom hydraulically driven feed rollers
- Dual horizontal chain flail drums (one stationary bottom, one carried by a floating yoke) with segmented drums; each equipped with eight flail chain rods
- Discharge system consisting of 62" (157.48 cm) x 22" (55.88 cm) opening and 61.5" (156.21 cm) x 11.5" (29.21 cm) hydraulically powered ram
- Flail Drum Speed: Adjustable from 0 to 578 RPM
- Feed Rate: Adjustable from 40 ft/min (12.9 m/min) to 145 ft/min (44.2 m/min)
- Remote control
- Hydraulic flail drive
- Light package
- 11-HP (8.2 kW) air compressor

## **OPTIONS INCLUDE**

• ESPAR heating system for cold-weather start



